Product Data Sheet
GW44904NWK
44 CE Range




44 CE APTA is the Gewiss range of junction boxes designed to adapt to different installation needs: to fit the environment, suit the application, and align with common installation habits. The range is available in three sizes (2K, 3K, and 4) and three colours (black, grey, and white) to meet different application and aesthetic requirements. 44 CE APTA offers six fixing methods for maximum installation flexibility, including external screw fixing with bracket included, internal screw fixing, knock-in fixing with threaded base, panel mounting, fixing with cable ties for trays or temporary structures, and the patented nail gun fixing system. A dedicated range of accessories further enhances installation speed, safety, and reliability, including terminal supports compatible with Wago 221-412, 221-413, and 221-415, as well as the patent-pending Earthing Clamp for metal cable glands used with armoured cables.

GENERAL INFORMATION	-	**MECHANICAL AND FUNCTIONAL CHARACTERISTICS**	-
Accordance with Standards	IEC 60670-1, IEC 60670-22	Lid screws (no. and type)	4 x 1/4 turn, captive, sealable
Application	Ordinary junctions	Captive lid	Yes
Internal dimensions BxDxH (mm)	100x100x52	Operating temperature	-25 +60 °C
External dimensions BxDxH (mm)	108x108x58	IP degree	IP66 (membrane) / IP67 (cable gland)
Material	PP + GF (case), TPE (membrane), PA + GF (bracket)	Glow wire test	750 °C (case), 650 °C (membrane)
Colour	White RAL 9016	Thermo-pressure with ball	85 °C
Lid	Low screwed	UV resistance	Yes (IEC 60670-22)
Type of bottom	Standard	Halogen Free	Halogen-free in compliance with EN IEC 63355
Walls	With threaded entries, membrane and knock-out	Cable entries on sides	7 x M20x1.5 threaded entries with Ø 3÷12 mm membrane 1 x M20x1.5 threaded entry with Ø 3÷12 mm membrane and Ø 25 mm knock-out
-	-	Cable entries on back	2 x Ø 3÷12 mm membrane entries
-	-	-	-
ELECTRICAL CHARACTERISTICS	-	**EQUIPMENT AND ACCESSORIES**	-
Insulation class	II (according to IEC 61140 standards)	Accessories supplied	Fixing bracket
AC Rated operational voltage (Ue)	750 V	Completeable with	GW44622 (double insulation caps), GW44741 (supporto connettori Wago 221)
Insulation voltage (Ui)	750 V		


BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Part	Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
		Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Propanol	Alcohol		
Case	Resistant	Limited resistance	Resistant	Resistant	Resistant	Limited resistance	Not resistant	Resistant	Resistant	Resistant	Resistant
Membrane	Resistant	Limited resistance	Resistant	Resistant	Resistant	Not resistant	Not resistant	Not resistant	Resistant	Limited resistance	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY



-25 +60 °C

IP

IP66 (membrane) / IP67 (cable gland)

GWT

750 °C (case), 650 °C (membrane)



85 °C



Yes (IEC 60670-22)



Halogen-free in compliance with EN IEC 63355



II (according to IEC 61140 standards)

STANDARDS/APPROVALS

CE UK CA