



## Product code

**VP37263**

### 63A 3P+E Interlocked Switched Sockets IP67

|   |
|---|
| ★ Rated current: 63A                                    |
| ★ Rated voltage: 380-415V                               |
| ★ No. of poles:   |
| ★ Earth contact position: 6H                            |
| ★ Color: Blue   |
| ★ Protection degree: IP67                               |
| ★ Housing material: Flame Retardant PA6 RoHS Reach      |
| Contact: nickel-plated brass RoHS Reach                 |
| ★ Operation Temperature: -25°C~+40°C                    |
| ★ Certificates: CE,ISO9001:2008,RoHS,REACH              |
| ★ Standards: IEC/EN60309-4, IEC/EN60309-1,IEC/EN60309-2 |

- > RAL 7035 grey, housing made of insulating material;
- > Flame and fire resistance, the base overcome the glow wire test at 850 centigrade;
- > Mechanical interlock enabling the switch to be operated only when it's plug-in, the plug can only be pulled out when the switch is on "O";
- > Switch with handle which can be padlocked from outside in position "O" and "I";
- > Switch is in compliance with IEC 60947-3, usable AC 21,AC 22, AC 23;
- > Mechanical protection degree is IK8.

| Dimension                    |  | 63A  |     |     |
|------------------------------|--|------|-----|-----|
| Current                      |  | 3    | 4   | 5   |
| Pole                         |  | 3    | 4   | 5   |
| a                            |  | 300  | 300 | 300 |
| b                            |  | 163  | 163 | 163 |
| c                            |  | 191  | 191 | 191 |
| d                            |  | 245  | 245 | 245 |
| e                            |  | 146  | 146 | 146 |
| Cable size(mm <sup>2</sup> ) |  | 6~25 |     |     |